

Patent Application of
Richard J. Ditzik
for

~~Modular Notebook and PDA Computer Systems for~~
~~Personal Computing and Wireless Communications~~

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
10240
10245
10250
10255
10260
10265
10270
10275
10280
10285

U.S. Patent 5,189,632 of Paajanen et al disclosed a hand held computer unit with an antenna and wireless RF communication capability, small flat panel display and a keyboard, in a partial clam shell type structure. However, they do not teach expandable hinge means, base station for handset relay functions, or cover latching function. U.S. Patent 5,327,486 of Wolff et al teach a conventional laptop computer with antenna and RF communications to a radio network and local exchange telephone network. However, they fail to teach expandable hinge means, edge hinge means, handset means or base station relay functions. U.S. Patent 5,459,458 of Richardson et al teach a virtual pager and data terminal system. However, they do not teach notebook like computers, base unit station or personal/PDA computing. U.S. Patent 5,008,927 of Weiss et al teach a computer and telephone system with a display screen on a conventional telephone structure keyboard unit. However they fail to teach notebook like structure, wireless communication or handset relay functions. U.S. Patent 5,196,993 of Herron et al teach a laptop computer with a removable flat panel display with built-in support feet for desktop support. However, they fail to teach expandable hinge means, exterior communications functions, cover latching functions or computer display assembly. U.S. Patent 5,200,913 of Hawkins et al teach a laptop computer with flat panel display and pen input means. However, they fail to teach expandable hinge means, edge mounted hinge or latching functions.

Wireless hand held computer devices, such as cellular and Personal Communication System (PCS) telephones, have limited display capabilities. Prior art wireless computer units have display screens that are small (1.5 - 2.5" diameter), and they lack interactive capabilities to be successful for text, graphic and video applications. Some prior art notebook and laptop computers have integrated wireless communication means, but they are too large and bulky to be successful for in mobile uses. Prior art wireless devices do a poor job of providing voice, data and video communication functions. Typical wireless computer systems have display screens that are too small and have limited computing power. Prior art laptop and notebook computers are too heavy to carry for long periods. Inventions herein solve these problems by embodying a unique relatively thin notebook-like computer system that is capable of: being: (1) opened like a notebook, (2) quickly disassembled and re-assembled, (3) used for handset/earset communications relay operations and (4) used in a wide variety of computing, collaboration, communications and conferencing applications.

Inventions described herein are based on several Disclosure Documents submitted to the U.S. Patent and Trademark Office, including Document No.s 353691, 363753, 368165, and 377365. Inventions herein solve several prior art shortcomings, resulting in new modular integrated computer systems. The inventions as described below can be quickly configured to desktop, notebook, wireless and/or PDA embodiments. Thus, the user will be able to purchase a single computer system and pay much less money than conventional systems.

SUMMARY OF THE INVENTION

An object of this invention is to provide a modular multiple function display-computer system, where one can use the same relatively high resolution color flat panel display in both a desktop and mobile environments.

5 Another object of this invention is to provide means to reduce the cost to the customer of owning several expensive computer systems, by combining in one system the capability of performing both office desktop and portable/mobile computing and communications applications. Thus the invention herein saves the user the expense of purchasing separate computer systems for desktop uses, notebook computer uses, PCS uses and PDA uses.

10 Still another object of this invention involves means to quickly configure a modular notebook or PDA-like computer system into a plurality of system configurations for personal computer and wide area communication operations.

15 Another object of this invention is to provide for a relatively thin and light weight computer unit to be carried under one's arm in a notebook-like fashion, yet have sufficient computing power to execute a wide range of conventional computer and communications applications.

Still another object of this invention is to provide for bi-directional communication of voice, audio, text, graphics, image and/or video data to wide area communications networks where one or more users may communicate with other users with appropriate apparatus. The communication may realtime or store forward type communications.

20 Another object of this invention involves hardware and program software to control cellular or PCS communications, combined with a light weight mobile notebook or PDA like unit. The unit or system would act as a computing platform and base communications relay station. The system or unit may then relay voice and data to/from a handset unit or earset unit, where the base unit relays the this voice and data information to/from a wide area communication network.

25 Still another object of this invention involves means for quick disconnection or disassembly and subsequent connection or assembly of key component of the system, such as battery power unit, communication adapters (modems) and/or wireless telephone units.

30 A still further object of this invention is to use the same display-computer system assembly, comprising of relatively large high resolution color flat display panel and a powerful CPU with large memory, etc., and combining them in a modular fashion with a thin keyboard, battery power source, modem, and wireless communications means.

Another objective of this invention is to provide means for integrated telephony functions on a portable computing platform, with powerful microprocessors running Windows operating systems for a wide range of computing and communication functions.

A still further objective of this invention is to provide for full Internet access on a wireless mobile platform, where the user can access the world wide web and execute most of the available Internet browser functions and plug-ins. The computer system would be capable of performing most of the Internet data access, download, upload and conferencing functions

BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 shows a perspective view of a portable computer with a notebook clamshell-like structure.
- 10 Fig. 2 shows a perspective view of a modular portable computer system in desktop configuration.
- Fig. 3(a) shows a notebook like portable computer in an open state.
- Fig. 3(b) shows the notebook like computer in a closed state.
- Fig. 3(c) shows a handset telephone unit and earset unit.
- Fig. 4(a) shows a notebook or portable computer with a protective covering material.
- 15 Fig. 4(b) shows an electrical power source unit.
- Fig. 5 shows a PDA like unit with a roughly transparent cover half.
- Fig. 6(a) shows a notebook or PDA in a partial open state.
- Fig. 6(b) shows the notebook or PDA in a reversed open state.
- Fig. 7 shows block diagram of the computer system and associated elements.
- 20 ~~Fig. 8~~ ^{Figs. 8A and 8B} shows a flow diagram of the computer system programs and operations.

DETAILED DESCRIPTION

Figure 1 shows a computer system, to be operated by a person or user, where the unit has a conventional notebook clamshell-like structure. The computer system as used herein can also be referred to as a portable computer system, computer-display unit or base unit, and shall also include the terms: personal computer, notebook computer, sub-notebook computer or Personal Digital Assistant (PDA). The computer system as disclosed herein typically comprises of a flat panel display assembly 2, which includes a display panel and screen 4 and other components described below. An expandable hinge means 10 connects the flat panel display assembly and cover assembly (8, 9 and 16). Expandable hinge means 10 may be embodied many ways including using flexible material that is corrugated, having its grooves running parallel to the edge of the notebook structure. Cover assembly may consist of two or more sections, such as a first cover section 8, second cover section 9, and a keyboard section 16. One or more of the cover sections may be quickly disassembled from each other by the user. To avoid accidental disassembly, means may be embodied where the user must simultaneously press two push buttons 5, for example one on each side of the structure, in order to disconnect the sections. The portable

portable computer system may also have an inside protective sheet member 4A attached to the inside the fold of the computer system. Fig. 1 shows a partially open notebook-like structure, but it may be closed all the way shut and secured, by a securing strap means 8A. This strap means may be secured to the other side of the display assembly 2 by Velcro like strips, for temporary securing and un-securing, with one's fingers. One purpose of this foldable embodiment is to provide the computer user with a handy portable notebook computer that: (1) when closed, one can easily carry, cradled in one hand under one's arm, and (2) easily opened for access to the computer indicators and controls.

The flat panel display assembly 2 may be a monochrome or color liquid crystal displays (LCD), such as those manufactured by Sharp Electronics, NEC Electronics, Toshiba Corporation or others. The display panels screen sizes may be 10 to 14 inches or more in diameter. The display pixel arrays may be 640 by 480 (VGA), 800 by 600 (SVGA), or 1024 by 768 (XGA). Color depth should be six bits, and the response time should be 45 to 50 milliseconds ($t_{on} + t_{off}$). Brightness of the screen should 70 Cd/m² and contrast ratio be at least 100:1, where 250:1 is preferred.

LCD panels from Sharp Electronics may be used in the embodiments. Applicable LCD Models include LQ11DS01, LQ12DS01, LQ12DX01 and LQ12X12. These panels have screen sizes of either 11.3 or 12.1 inches measure along their diagonal. Each panel is capable of a color depth of 6 bits/sub-pixel, a response time of 80 ms, brightness of 70 - 150 cd/m² and a contrast ratio of 100:1. LCD panels from NEC may also be used, such as NL10276BC24-04, NL8060BC31-02, NL8060BC31-01, and NL8060BC29-01. These panels are capable of 6 bit color depth, 50 ms response time, 70 cd/m² brightness and 150:1 contrast. Toshiba panels that may embodied include: LTM11C016, LTM12C236, or LTM12C25S, which are capable of 50 ms response, 70 cd/m² brightness and 100:1 contrast. Manufactures' references and manuals for each are hereby incorporated by reference.

Several I/O slots and/or connectors may be embodied at one or more edges of the flat panel display assembly 2. Fig. 1 shows access slots to a floppy disk 28, external communication means 27, printer connector 31. Other external connection means may be embodied. Several connector means may be embodied, including auxiliary video connector, COM ports, and/or mouse/game ports. PCMCIA PC card 40 may be included for adding fax/modem, network interface (wire or wireless) external communications and/or added memory. An integrated built-in transmitter receiver and a retractable antenna 32 may be embodied, for example to the flat panel display assembly 2. The antenna and associated RF transceiver may be used for wireless communications to/from an external communication network. Many of the well-known notebook computer or personal computer I/O devices may be embodied.

An important feature of this embodiment is the dimensions of the computer-display unit. It may be made conveniently larger than a 8.5 X 11 inch sheet of paper, so that one can place one or more sheets of paper (or other relatively thin flat objects) inside the closed clamshell like notebook structure in a folding or latching fashion. The user can safely carry papers from location to location without folding or wrinkling them. Thus the unit can act as a carrying device as well as a notebook computer. The outside surfaces and edges of notebook computer may be covered with leather, vinyl of other type of soft material, for easy of hand carrying and surface protection. Other parts may be embodied including foldable short legs 9A and 9B, keyboard resting pads 16A and 16B, built-in audio speaker(s) 30.

Fig. 2 shows the portable computer with several parts detached or disassembled. This embodiment may be used in desktop computer system environments. The flat panel display assembly 2 may be placed at an inclined angle, with foldable leg support means 19A and 19B. The leg support means may fold relatively flush to the backside of the assembly 2 (motion range A) when not in use, via a simple hinge 15. Vertical portions 19A and 19B may slide in and out, in a telescoping type arrangement, to allow wide range inclination angles. A pair of short legs 3 may be placed near the front of assembly 2 that may also fold relatively flush with the back of the assembly. Means may be included to place the screen at a vertical orientation. A pen or stylus input means may be associated with the display screen 4. The pen or stylus means may include finger input (touch panel) means, where one can write or point to area on the display screen. The expandable hinge means 10 may be removed from the assembly 2 and from the cover section 9 by a quick disconnect or disassembly means 5. Alternatively, the hinge means may be fixed to parts 2 and 9. The hinge means may be made of a relatively flexible material, such as leather and vinyl. It may be corrugated as shown in the figure so it can bend easily and expand, as required. The hinge may have a number of attachment slots 12 for the quick dis-attachment or disconnection from hook mechanisms 13. Fig. 2 shows the flexible hinge means 10 removed from the other assemblies.

Cover section 9 may contain a battery power unit containing one or more batteries and power circuit elements. The battery power unit may be embodied with several types of batteries, including Lithium- ion or NiCd batteries. The power unit may be a self contained battery package, having an easy to read charge indicator 22 that indicates the state of the battery's electrical charge. Because all batteries have a limited useful charge life, the package may be easily and quickly disconnected from the keyboard section 16 and replaced with another battery package. Spare battery packages and other spare parts could be carried in a separate traveling case (not shown). The keyboard section 16 may have a full size QWERTY keyboard with movable tactile keys. An electrical cable 20 may connect the keyboard to the computer-display assembly 2. Although short cable is shown, it may be a long cable or a flexible cable, so that the keyboard may be moved about if desired. Alternatively, a wireless electro-magnetic link may be embodied

such as infrared (IR) or RF links, which would replace electrical cables 20 and 26. The cover section 8 may contain a wireless handset 14, such as a cellular telephone transceiver. The handset may have retractable antenna, small speaker, keypad, built-in microphone and a battery source. This handset 14 may be capable of analog or digital cellular operation, including AMPS, TDMA, CDMA, PCS, CDPD, or equivalent types for communicating with wide area wireless communication networks. The wireless unit 14 can be easily removed from a cutout or recess area 34 in the cover section 8. The recess area is made slightly larger than the outside dimensions of the handset 14, so it can fit inside the recess with a relatively snug fit. It is important the handset be easily and quickly removed and replaced in the base unit. Alternatively, cover section 8 consist of the handset itself, so that a separate cover section with recess would not be required.

The portable computer system's flexible hinge and the cover sections should be made relatively thin so that when the two halves are folded (rotated) closed, it will not be too thick or heavy to carry with one hand. As shown in Fig. 1, legs 3, 5, 19A and 19B may be folded roughly flush with outside surfaces of the unit. The number cover sections are not limited to three. The cellular handset is shown in Fig. 2 may be connected to the computer system by an optional electrical cable 26. A RF transceiver in the wireless telephone would serve as the transceiver for the computer as well. This embodiment might be desirable to reduce the overall cost of the system. However, a wireless RF transceiver and modem may be located in the flat display panel assembly 2 for voice or data communications. An antenna may be embodied on the display assembly 2, with a retractable antenna 32. The display assembly may include the computer system located within the assembly housing. The advantage of this later embodiment is that the telephone 14 and computer system could be operated independently.

The portable computer system may also have means for connection to a non-battery power source, as shown in Fig 2, via a standard power line cord and plug 28. The system may also have means for connection to an external wire based wide area communications network 33, via cable 29. The wire based wide area network may include one or more telephone networks, cable TV networks and/or computer LAN/WANs. Telephone networks may include POTS, ISDN, ATM or other equivalent types. Several computer interface connection means may be embodied, for example interface slots/connectors as shown (27, 31, and 38). These interfaces might include R/S 232, USB, IEEE 1394, PCMCIA, or other computer I/O (serial or parallel) connections. Useful connections may include a bus extender connection, so that the notebook computer can be interfaced to another more powerful computer. For portability reasons, it is desirable that the modem or digital terminal adapter be built into the computer system unit. Some means for software loading should be included such as a floppy disk or smart card. Internal mass memory of the computer system could include ROM, flash memory, or other memory means. Means for accepting PCMCIA cards, ROM cards or other types of memory card may be implemented.

Preferably, the system may be embodied with a very small light weight and low power mini hard disk. One or more IR communications interfaces may also be implemented.

Other capabilities such as FAX send/receive, speech recognition, voice processing voice mail, telephony, and E-mail functions may be implemented in the computer system. A built-in microphone 36 and speaker 30 may be embodied to support speech input/output and multimedia functions. Preferably the display should be capable of full color with a wide viewing angle. If the display is back lit, the user should be allowed to switch the backlight "on", "off" and to a multiplicity of levels in between. The operating system of the notebook/PDA should be a GUI type such as Windows™ 3.1/95, Windows CE™, MagicCap or another suitable GUI based computer operating system. The system should can be designed to support wide range of communication connectivity and software compatibility.

a Figs. 3A and 3B show another embodiment of invention having a base unit or notebook computer system 100, a handset unit 14 and a earset 34. This embodiment shows a relatively thin flat display panel assembly 2 having a display screen 4. The system may also include a pen and/or finger input means 7. The base unit has an expandable hinge means 10 physically connecting the display assembly to the other half of the base computer unit. The other half can be comprised of several sub-assemblies including a battery power source section 9, keyboard assembly 16 and an electronics housing section 8. The keyboard assembly contains a keyboard unit 16A, which may contain a full-size QWERTY keyboard unit. The housing section 8 may include a wireless modem or communications adapter means. The expandable hinge means 10 should have an easy access locking and unlocking means 10A, which can temporarily lock the rotation of the two halves at the user's desired angle. Electronic housing section 8 may be attached edge wise to the keyboard assembly 16 by a quick attach and release connection means. As shown in the figures, several assemblies can be disassembled by pressing one or more finger access tabs 5. Likewise, a battery source section 9 may be edgewise connected to the opposite edge of the keyboard, via similar quick attach and release connection mechanism having finger push tabs 5. The tabs may be located on each side of the assemblies for quick and easy, but safe, user disassembly. The connection means may include means for secure physical attachment and connection of electrical wires, located inside the subassemblies. Although the sections may be ridge, the attachment mechanisms may be may somewhat flexible, elastic or pliable, so that the combination of assemblies can bend slightly.

Battery power source unit 9 may consist of one or more batteries with voltage regulation, AC/DC operation, power management circuits and charging circuitry. In a preferred embodiment the unit should be capable of accepting electrical charge from an AC line. A important feature embodiment of the invention is means for quickly interchanging an electrical power depleted battery power unit 9 with a freshly charged battery unit. This may be accomplish

by a combination of finger push tabs 5, latches and hook means for quick disconnection and re-attachment. In one intended scenario a user may carry several spare battery packages in a separate briefcase. When the attached battery package is depleted, the user can quickly changed out the battery sections. The user can then plug the depleted battery package into an AC line for a built-in charging operation.

It is preferable that each of the major assemblies and sub-assemblies be made relatively thin for easy carrying. The expandable hinge means should be made somewhat flexible, elastic or pliable so that the user may place relatively thin flat objects inside the folded space of the notebook-like unit. These thin objects may include sheets of paper, cards, brochures, or similar relatively thin flat items. Linkages between the sections may be made somewhat yielding, pliable, elastic and/or stretchable. Although the display device may be ridged, the other half of the notebook may be embodied with thin flexible enclosures and other structural components. Also, the flat panel display device and assembly 2, 4 may be made flexible. Thin and flexible keyboards are known to those in the art. The other parts may be adapted to have thin and slightly flexible mechanical features. The two halves can be closed by hand and secured by a flap and snap means 43 or equivalent means. As discussed above, the expandable hinge means 10 may be made flexible and expandable by incorporating a multiplicity of small folds or other equivalent means. If the user places thin objects between the halves of the base unit, one or more sides could bulge out slightly, improving the physical object carrying capability of the notebook computer. This object carrying capability is an important feature for mobile users who may be carrying the notebook almost everywhere they go. The user may securely place and latch paper sheets, letters, memos, or other flat objects inside the notebook clam shell structure. A base unit hinge locking and unlocking means 10A may also be embodied, so that the user can quickly and easily temporarily lock the two halves of the unit to a rotationally fixed state (and later un-lock them).

Fig. 3(a) also shows several other elements including a small CCD video camera 46, built into the display assembly for video conferencing and other uses. One or more built-in audio microphones 36 may be embodied in the base unit. Preferably one microphone should be located on the edge of the notebook, as shown, so that the user may be in voice communications with other while the unit is closed. One or more audio speakers 30 may be built into the base unit. One or more compartments 47 and 48 may be embodied at convenient locations to store attachments for use with the mobile computer system. A telescoping antenna 32 may be embodied into the base unit as shown, or it may be built-in the unit and not exposed. Although the base unit 100 can be a self-contained unit, it may work with other optional attachments, such as a wireless cellular-like handset 14 or earset 34. The handset 14 may operate roughly equivalent to conventional cellular telephone handsets with a built in power source, providing voice and/or data communications to wide area communications networks. The earset 34 has a small low power

RF transceiver, audio microphone, audio speaker and small battery source, which is capable of fitting into the user's ear. The wireless earset unit may be used for hands free applications. The user may then walk around while communicating with the handset or earset. If one is using the earset he/she may also use a pen input means 7 or keyboard 16 while in audio communications.

5 For semi-private voice communications, some users may prefer using the handset 14, with handset speaker 14A, handset key pad 14B and handset microphone pickup 14C

If one is using the handset or earset, the base computer unit 100 may be placed some distance away from the user, typically in the same room or nearby room. The base computer unit may be designed for a higher transmitting power level. The base unit may be designed to allow the user to switch between a high or low level transmitting and receiving power levels. The earset 34 or handset 14 can be designed for a much lower RF transmit and receiver electrical power levels, because the base computer unit 100 can be place a relatively short distance away (typically from a few feet to about fifty feet). Thus, the base unit 100 may relay RF communications between the handset or earset and an external wide area communications network. The base unit could safely embody a more powerful RF transmitter resulting in a larger signal to noise ratio. This will result in improved wireless communication to and from wide area networks that may have antennas several miles away. A very important advantage of this invention is that the user has the option of having very low electrical power electromagnetic fields near his/her's head, thus improving the health and safety aspects for the user. Since less power is required for the handset 14, it can be thinner and smaller than a standard cellular handset. Thus the handset can be smaller and easier to place in the user's pocket. The earset can be made very small so that the users can leave it in his/her's ear for long periods of time and have one's hands free for other uses.

Fig. 3(b) shows the base unit computer-display unit 100 in a closed configuration, in which one may carry it under one's arm. Since the unit is typically battery powered and contains electronics for a wireless voice and PCS like operations, one could use it for voice/data communications while carrying it about (i.e., in transport). The user may speak towards one or more microphones 36 located along the top edge. The user will be able to hear the other person(s) talking, through audio speakers 30 located conveniently on the base unit. A small telephone keypad could be located behind a protective door 41, for convenient dialing of a telephone number. The door may be a simple sliding door device or mechanism. The antenna 32 may be a sliding telescoping type. A simple display indicator 22 may show the electrical charge state of the battery source. A plurality of switches and indicators 46 may be located along one edge of the base unit for easy viewing and access. Such switches and indicators may include: an On-Off switch, Mode Switch (for voice, data, and video modes, etc.), high/low power transmit switch, ring/alarm mode and/or speaker/mic mode (for earset, handset, etc.). For securing the two halves of the base unit, a flap 43 made of a simple expanding material, which may include a snap means at one end and may be secured with a pin and/or pivot means. The flap would then

snap to secure the flat panel display assembly 2 and cover assembly (9, 16, 8). In Fig. 3(a), the flap 43 is shown rotated in the opposite orientation for clarity only. Other securing means may be embodied that are known to those in the art.

5 Fig. 4(a) shows the portable computer system or computer-display unit 100 covered with a thin soft protective material or film, such as leather or vinyl. This material will protect the unit when it is bumped and/or banged into hard objects while in the use in field or office environments. The protective material may have a texture or roughen surface (as indicated in the figure), which would also provide for a relatively high mechanical friction; so it will be easier to
10 carry under one's arm. Holes or cutouts may be embodied in the protective cover for viewing and/or using the various indicators, switches and keypads. A zipper securing means 45 may be embodied with the notebook, as shown in Fig. 4(a). The zipper means may be attached to the leather or vinyl covers so that the unit can be zipped closed to secure and protect objects placed inside the notebook. A pull tab 45A of the zipper means is shown in the figure. This embodiment
15 would be especially applicable in rugged or harsh environments. A strap 50 may be attached to the unit so that the user may temporarily store it on a hook for example. Fig. 4(b) shows an embodiment of the battery power source section 9. As in previous embodiments, it may be detached from the notebook computer-display unit. A spring loaded pull out power cord 9B may be embodied, so that the user can conveniently pull out the power cord to electrically charge the package. The power cord and plug may be easily retracted inside a cutout space on the side of
20 the subassembly. Several adjunct attachments and/or accessories may be carried in small compartments in the notebook unit. In addition, accessories and attachments may be carried in a separate briefcase or like carrying case (not shown in the figures). Such accessories may include a line power supply and cord, extra battery power source section 9, spare earsets 34, spare
25 handsets 14, external hard drive, external CD ROM drive, external mouse, spare styluses and/or spare video camera/lenses 46.

An important advantage of this notebook computer unit invention is that it can be operational when it is in the closed configuration. Thus, while carrying the unit in one's hand or under one's arm, the user can perform voice, data and/or video communications. The notebook
30 unit can be used in an open configuration on a desktop, airline tray or wide variety of other computing environments. The unit can be configured for wire based or wireless communication operations. The unit can be used for general purpose computing, network computing, pen input computing, PCS/Cellular, data/video conferencing, on-line network computing and data collaboration applications. The notebook unit can be used as a personal organizer or personal
35 information manager, such as a computer equivalent of the Franklin Planner™ or equivalent planners. A multiplicity of personal computing applications may be embodied on its computer. The unit may be capable of wire or wireless communications, linking it to multiple handsets and earsets. The notebook computer unit may have a plurality of electrical connectors along the edges

or other convenient locations for connection to a plurality of external devices, including but not limited to: modems, network interface cards, hard disks, floppy disks, and bus extender enclosures.

5 Preferably the notebook assemblies should be made relatively thin and light weight that would be an advantage in mobile use. For example, the flat panel display assembly 2 should have a thickness of roughly 0.75 inch or less. The cover assembly may be comprised of the battery power source section 9, keyboard assembly 16, and external communications section 8 should have a thickness roughly 0.75 inch or less; so that the folded total thickness of the unit could be 1.5 inches or less. However, an overall thickness of one inch (i.e. 0.5 inch for each half), or less, may be preferred. A keyboard unit located in keyboard section 16 that may be 10 Model KFNR available from Alps Electric Co. Ltd. This keyboard unit has a thickness of 10 mm, a 3 mm key travel, a 1 mm over travel and a minimum key pitch of 18 mm. Alps Electric also has introduced a 7.5 mm height keyboard assembly a full size keyboard, capable of high speed typing without operator tiring.

15 Fig. 5 shows another alternate computer notebook embodiment, consisting of a somewhat smaller size flat panel assembly 2, display screen 4, pen/stylus means 7 and a roughly transparent display panel cover 17. The flat display panel could be an LCD, FED, or other type of flat panel display. The panel cover 17 could be made of a hard rigid material or a durable soft polymer material that is roughly transparent to a range of electromagnetic radiation frequencies. This 20 cover may be made optically transparent to let the ambient room light to impinge onto a plurality of photoelectric light sensors 41A, 41B and 41C, which may be placed onto the display panel assembly 2. The photovoltaic or photoelectric light sensors may convert ambient room light to electrical voltages. These sensors may provide power energy to power the unit. The sensors may also help change the unit's battery source. Thus, with the roughly transparent cover 4 closed over 25 the display panel assembly, some light rays will be transmitted through the cover. Photons from the ambient light are converted to an electric voltage, via the sensors and energy conversion circuitry that is applied to the computer unit's power source. Even if the computer unit is turned off and cover closed, the sensor could still be charging its batteries. The roughly transparent cover 17 may be made flexible layers of polyester, polycarbonate or other suitable materials. An 30 advantage of this embodiment is an improvement in maintaining power to the notebook unit for longer periods compared to prior art battery powered units. Information on the display screen may be viewable even with the cover 17 is closed over the flat panel display assembly 2. Viewing of the display screen with the cover closed is an improvement over the opaque covers of conventional notebook computer and PDAs.

35 Fig. 6(a) shows another embodiment of a thin light weight notebook computer or PDA unit. The cover panel 17 contain a keyboard 16A, which may be a membrane type keyboard.

The flat panel display assembly 2, with its display screen 4, is attached to the cover panel 17 by an expandable hinge means 10. The hinge means, which may be elastic or pliable, should be capable of being rotated over angles A. The hinge means should be capable of rotating through roughly 360 degrees, so that the two halves may be folded back onto each other as shown in Fig.

5 6B. In the configuration of Fig. 6B, the notebook unit can be held in one's arm, and the display screen can be written onto by a stylus or pen. The unit could also be placed onto the table or desk for convenient viewing. The cover keyboard assembly 17 can be closed to hold loose sheets of paper, brochures, etc. In this latter case, the size of the panel halves should be slightly larger than 8.5" by 11" to facilitate one carrying loose sheets. Expandable hinge means 10 is designed to
10 expand to accommodate a relatively thick stack of documents. Hinges may be made of pressed pliable corrugated plastic sheets can accommodate 0.5 inch or more gaps.

Various battery power sources 9 may be used in the above embodiments, including smart-battery technology having rechargeable batteries. They may be made capable of monitoring themselves for electrical charge level. Batteries that are suitable for this smart battery
15 technology include nickel-metal hydride (NiMH) and lithium-ion (Li-ion) types. NiMH batteries are more sensitive to overcharge than NiCd batteries. Care must be taken to avoid overcharging that causes heating, which is damaging to the NiMH cycle life and capacity. Li-ion batteries require tight battery management for safety purposes. NiMH batteries are available from Sanyo Energy USA. Several power management and smart-battery devices are available. Duracell has a
20 smart rechargeable battery with intelligent power management circuits for charge level gauge means, as disclosed above. The gauge may constantly show the state of the total battery charge. Advantages of an intelligent battery management system include customer notification of charge state, longer mobile operation times, longer battery lifetimes, and faster charge times. The rechargeable battery and power management circuit may collect and communicate the present and
25 predicted battery data to the host notebook computer under software control.

Wireless communications adapters or modems disclosed in the above embodiments may consist of analog or digital transmitter and receivers, having control circuitry for cellular AMPS, PCS, CDPD, and RF links to wide area communication networks. The communication means
30 disclosed herein may make use of long distance or short distance communications techniques, methods and equipment. Communication techniques may include several types of digital multiplexing and command access schemes such as TDMA, CDMA, GSM, or a combination thereof.

Fig. 7 shows a block diagram of the system elements and associated circuitry, hardware, firmware and software. A microprocessor 38 controls most of the system elements. A
35 computer system I/O bus 60 is shown interfacing several system elements. Many types of microprocessors may be embodied, including 16, 32 or 64 bit processors. The microprocessor

may a complex instruction set computer (CISC) or a reduced instruction computer (RISC) computer types, or a combination of the two. CISC microprocessors that may be embodied, including the Pentium P5 manufactured by the Intel Corporation, the 68000 series microprocessors made by Motorola Corporation. Many types of RISC processors may be embodied, including the ARM series, the UltraSpac by Sun Micro Systems, the SH Series by Hitachi, PowerPC by Motorola and IBM and the MIPS R4000 series by several sources. The above manufactures' references and manuals are hereby incorporated by reference. Since electrical power dissipation is very important in portable systems, RISC microprocessor may have an advantage with smaller transistor counts, low voltages and fully static designs. RISC processors are available at an operating voltage of only 2.0 volts. RISC processors using 0.5 micron CMOS processes have resulted in die sizes for core functions of roughly 4 mm². RISC processors can deliver 300 - 400 Mips/W. Microprocessor 38 may support several types of I/O buses (typically 32 bit wide), such as VL or PCI type buses. Microprocessor and I/O busses are well known to those skilled in the art.

A Microsoft Corporation's Windows® operating system software may be embodied in the computer system. For these systems, the microprocessor CPU should be at 32 or 64 bit processors, capable of clock speeds in the 100MHz or more. The microcomputer system may also consist of one or more I/O port means 62. A PC Card interface 27 may be embodied for bus expansion, extended memory or other added circuitry having access to the main bus 60. A mass memory device 42 may be embodied in the system, which typically is a magnetic disk memory hard drive. Many devices may be connected to the computer system, including a smart card interface 46 and keyboard 16. A touch panel and pen input means 7 may be embodied in the system, which may be separate or integrated. Examples of such touch pen devices are available from Elo Touch Systems Inc. in Oak Ridge, TN, MicroTouch Systems Inc. in Methuen, MA, and Carroll Touch Corp. in Round Rock, TX. Pen and touch panel combinations means are available from Scriptel Corp. in Columbus, OH for the tablet, and Symbiosis Logic in Colorado Springs for an IC controller. Other pen and touch devices are available from Phillips Semiconductor, Sunnyvale CA. Other more traditional cursor control devices 56 may be embodied, such as a mouse, trackball, touch pad, or force transducer. Preferably, most of these components should be sufficiently small as to fit into relatively thin display assembly 2.

The flat display panel device 2 is be interfaced to the system bus 60 through display controller circuitry 44. Preferably, the display controller should be capable of VGA or SVGA display formats. Integrated into the display controller may be a BitBlt engine (to accelerate graphics), RAMDAC memory, clock synthesizer and display frame buffer. A digital signal processing (DSP) co-processor 48 may be embodied. The DSP may accept data from many sources including a microphone 36 and video data source 43. The DSP or microprocessor may output signals to one or more audio speakers, as shown as 10A and 10B. Video data may be in

either analog or digital form. Microphone 36, and speaker(s) may be embodied in the handset or earset of the previous figures. Video data may be pre-processed by a the DSP. Video sources may include output from video cameras, VCR, broadcast TV, satellite TV or cable TV.

External communication means 54 may be connected to the bus, which may be capable of fast two way data transfers. The communications means 54 should be capable of controlling communications to and from a plurality of wire and wireless communication systems. These include wire based telephone means 53 and wireless communication means 51. The system may include an antenna means 32 for transmitting and receiving electromagnetic radiated signals. External communication means may be connected to one or more information or communication service providers. These service providers may include telephone services (RBOCs, LEC), on-line computer networks, Internet service providers, cable MSOs and/or long distance telephone firms. They also may include cable TV companies, satellite TV service, and LAN/WAN communication network providers. The external I/O port means 62 may be connected to a Universal Series Bus (USB) and/or an IEEE 1394 (Firewire®) type I/O bus.

Fig. 8 presents a typical flow diagram of computer programs executing in the system of the embodiments disclosed herein. After a power-on action 60, the system may enter a standby power on mode 62. A power management program 66 may then be execute followed by a self diagnostic routine 68 that tests the major hardware and firmware elements of the system. If the test fails, a failure report 66 may be generated and either displayed or stored. If the test passes, the operating system (OS) 70 may be loaded and executed. With the OS loaded successfully, the system waits for incoming data and/or voice calls 72. The system may automatically enter a default system mode, or the user can select one or mode computer or communication modes 76. The user has the option of selecting several operating modes, which may include a conventional computing mode 78, a wireless data communications mode 80, and a wireless voice communications mode 82. A conventional computing mode includes typical PC computing or PDA computing. While in any of the above modes, base unit to external communications operations 79 may be controlled, which includes data/voice wire and wireless options. Control code 81 may control the bi-directional handset or earset to base unit communications operations. These operations may execute roughly simultaneously or on a time shared bases, as indicated by connection 83. Under program control, either the wireless handset or the earset may communicate data first between the base unit, then the base unit may relay the data to/from the external communications network. The above communications may involve two way or bi-directional communications, including many types of data (including text, voice, graphics, video and/or images).

Many types of computer application programs may be executed by the computer system. For example, one or more telephony programs 84, office/personal productivity programs 86, electronic mail or voice mail 88, and Internet/Web browsing programs 90 may be used. Other

PDA, PC or workstation programs may also be executed. One or more programs (algorithms or routines) 96 may be used to control this multiple program or system modes; this may include program coordination, scheduling and execution. Programs to control the mobile communications relay functions 98 may be embodied. Users may have the option to exit the application programs 100. Typically, after the applications have been closed, the user may exit the operating system 102. After the system exits the OS, the system may still may be in a standby power mode 104, in which the system can answer and process incoming calls, plus service other requests for other processing tasks. Users may have the option of turning off (or removing) all power to the unit 106.

10 It should be further understood that, although a preferred embodiment of the invention has been illustrated and described herein. Changes and modifications can be made in the described arrangements without departing from the scope of the appended claims. Other embodiments, additions, and improvements will be obvious to those with an ordinary skill in the relevant art.